



## Manual Closing Double Sliding Door

### Standard Features

- Custom width for precise fit to most any opening
- No threshold design
- Sturdy aluminum frame
- Magnet catch to hold door closed
- Fire rated clear paneling
- Tight tolerances

### Custom Options

- Digital lock
- Custom colors
- Aluminum handles
- Custom logo
- Corrugated paneling

***Custom  
designed and  
built specific  
to the  
constraints  
of the  
installation***



### Contact Info

801.494.2098

435 W. Airport Rd Unit A5  
Heber City, UT 84032

info@theWindChill.com  
www.WindChillEngineering.com

# Technical Data

## Double Sliding Door

Manual Closing



## Standard Specifications \*

| Size and Finish                             |                                       |
|---|---------------------------------------|
| Fits Aisle openings                         | 38" to 62"                            |
| Total Height                                | Up to 101 1/2"                        |
| Pass Through Height                         | Up to 98"                             |
| Total Width                                 | Up to 96"                             |
| Pass Through Width                          | 42"                                   |
| Profile Width                               | 3 11/16"                              |
| Standard Finish                             | Satin Anodize (Clear)                 |
| Upgrade Finish                              | Custom Anodize and Powder Coat Colors |
| Door & Frame                                |                                       |
| Material                                    | 6560 T-6 Temper Aluminum              |
| Tensile Strength                            | 30,000 psi                            |
| Paneling - Lexan (High Optic Polycarbonate) |                                       |
| Material                                    | Polycarbonate                         |
| Color                                       | Clear                                 |
| Odor  | Odorless                              |
| Thickness                                   | 4.5 mm                                |
| Self-ignition Temperature:                  | 650°F                                 |
| Meets or exceeds ASTM E84                   |                                       |

\* Custom sized doors available upon request

