



Rigid Walls


Standard Features

- Clear fire-rated paneling
- Sturdy aluminum frame
- Custom built to specification
- Tight tolerances for precise fit

Custom Options

- Custom colors
- Custom logo
- Corrugated paneling
- Brush along edge

***Custom
designed and
built specific
to the
constraints
of the
installation***



Contact Info

801.494.2098

435 W. Airport Rd Unit A5
Heber City, UT 84032

info@theWindChill.com
www.WindChillEngineering.com

Technical Data

Rigid Walls

Standard Rigid Wall

Size and Finish	
Max Size	50 x 98
Profile Width	1 ³ / ₁₆ "
Standard Finish	Satin Anodize (Gray)
Upgrade Finish	Custom Anodize and Powder Coat Colors

Standard Specifications

Expandable Rigid Wall

Size and Finish	
Max Open Width	94"
Max Closed Width	50"
Max Height	98"
Profile Width	2 ¹ / ₂ "
Standard Finish	Satin Anodize (Gray)
Upgrade Finish	Custom Anodize and Powder Coat Colors

All Rigid Walls

Door & Frame	
Material	6560 T-6 Temper Aluminum
Tensile Strength	30,000 psi
Paneling	
Material	Polycarbonate
Color	Clear
Odor	Odorless
Thickness	4.5 mm
Self-ignition Temperature:	650°F
Meets or exceeds ASTM E84	

